

INDUSTRIAL UL LISTED FIRE HOSE

06 FH62UL SINGLE JACKET (150 PSI)

06 FH64UL SINGLE JACKET (200 PSI)

06 FH67DUL DOUBLE JACKET (300 PSI)

FEATURES

- All Synthetic White Polyester Jacket. Internally EPDM Rubber Lined
- Choice of Single or Double Jacket
- High Strength. Cost Effective and Durable.
- No Drying Required
- Easily Maintained. Small Coil Size
- Standard White colour.



Progard UL listed Industrial Fire Hoses consist of 100% woven polyester filament single or double jacket with a low friction loss internally smooth EPDM rubber lining. These hoses are ideal for fire fighting applications where an approved working pressure rating is preferred.

Ideal for wash down hosing, first-aid fire fighting, fire brigades and industrial users. The hoses are available in white 1½" or 2½" diameters. Available in standard 50, 66, 75 and 100 feet hose lengths (15, 20, 22.8 and 30 metres). Approved and listed with UL.

Standard with 1½" or 2½" American NHT brass screwed couplings. Options: wire-on British aluminium alloy or brass instantaneous couplings (to BS336). Other types of couplings including German storz are also available upon request.

Technical Information

Product Code	Internal Diameter		Hose Type	Recommended Working Pressure	Test Pressure	Bursting Pressure
	inch	mm		PSI	PSI	PSI
06-FH62UL	1½	38	Single	150	300	450
	2½	64	Single	150	300	450
06-FH64UL	1½	38	Single	200	400	600
	2½	64	Single	200	400	600
06-FH67DUL	1½	38	Double	300	600	900
	2½	64	Double	300	600	900

Ordering Information

The following details should be specified with order:

- 1) Product Code
- 2) Single or Double Jacket and Hose Working Pressure
- 3) Hose Diameter and Length
- 4) Size and Type of Couplings including Material