

FIRE HOSE REEL



FEATURES

- Side Plate powder painted finish red
- Automatic hose reel has integrated automatic stop valve which will open after 2 revolution of the reel
- Threaded Inlet connection
- Outlet connection for hose can be rotated for left and right direction
- Waterways made from non ferrous metals which ensure corrosion free*
- Maximum working pressure 15Bar, test pressure 20bar
- Side plate available in stainless steel *(EN671 Approved models)

SRI fire hose reels are tested and approved to European Standard EN671 by British Standards Institution and to Australian Standards AS1221 by QAS Australia.



Code No.	Drum Size	Hose Diameter x Length	Distance Between Drums	Type
SIRIM, PSB approved BS EN671-1				
HRS038-SS-022-RD	22"(559mm)	25mm x 30m	350mm	Swing Manual



Code No.	Drum Size	Hose Diameter x Length	Distance Between Drums	Type
HRS038-MS-022-RD	22"(559mm)	25mm x 30m	350mm	Swing Manual
HRS038-MS-722-RD	22"(559mm)	25mm x 30m	290mm	Swing Manual
HRS038-MS-019-RD	19"(483mm)	25mm x 30m	350mm	Swing Manual
HRS037-MS-019-RD	19"(483mm)	19mm x 30m	350mm	Swing Manual
HRS037-MS-022-RD	22"(559mm)	19mm x 30m	350mm	Swing Manual
HRS036-MS-022-RD	22"(559mm)	25mm x 30m	310mm	Fixed Manual
HRS036-MS-722-RD	22"(559mm)	25mm x 30m	240mm	Fixed Manual
HRS036-MS-019-RD	19"(483mm)	25mm x 30m	310mm	Fixed Manual
HRS035-MS-019-RD	19"(483mm)	19mm x 30m	310mm	Fixed Manual
HRS035-MS-022-RD	22"(559mm)	19mm x 30m	310mm	Fixed Manual
HRS061-MS-722-RD	22"(559mm)	25mm x 30m	290mm	Swing Automatic
HRS060-MS-719-RD	19"(483mm)	19mm x 30m	290mm	Swing Automatic
HRS056-MS-722-RD	22"(559mm)	25mm x 30m	240mm	Fixed Automatic
HRS055-MS-719-RD	19"(483mm)	19mm x 30m	240mm	Fixed Automatic



Code No.	Drum Size	Hose Diameter x Length	Distance Between Drums	Type
BSI approved BS EN671-1				
HRS033-SS-022-RD	22"(559mm)	25mm x 30m	290mm	Swing Manual
HRS034-SS-022-RD	22"(559mm)	19mm x 30m	290mm	Swing Manual
HRS031-SS-022-RD	22"(559mm)	25mm x 30m	240mm	Fixed Manual
HRS032-SS-022-RD	22"(559mm)	19mm x 30m	240mm	Fixed Manual
HRS029-SS-022-RD	22"(559mm)	25mm x 30m	290mm	Swing Automatic
HRS030-SS-022-RD	22"(559mm)	19mm x 30m	290mm	Swing Automatic
HRS027-SS-022-RD	22"(559mm)	25mm x 30m	240mm	Fixed Automatic
HRS028-SS-022-RD	22"(559mm)	19mm x 30m	240mm	Fixed Automatic
AS APPROVED TO AS1221				
HRS035-GI-019-RD	19"(483mm)	19mm x 36m	310mm	Fixed Manual
HRS037-GI-019-RD	19"(483mm)	19mm x 36m	350mm	Swing Manual
HRS154-MS-600-RD	600mm	19mm x 36m	210mm	Fixed Manual